

Elixo 500 3S RTS / Elixo 500 3S io



Motorization for sliding gate

UP TO 8 M | 500 KG



Motor ground fixation



Reliable, hard-wearing, silent for sliding gates

- **Robustness** for gate up to 500 kg in residential or commercial.
- **Self learning programming system:** Autoregulation of speed and torque in relation with the gate weight (24V version only).
- **Intuitive programming interface:** Direct view on a large LCD screen to facilitate parameters modification (24V version only).
- **Compatible with solar system:** No need for power supply (24V version only).
- **Backup battery pack** (option) in case of power failure (24V version only).
- **Technology io-homecontrol**

Technical characteristics

	ELIXO 500 KIT STANDARD 24 Vdc	ELIXO 500 3S io
Motor power supply	24 Vdc	24 Vdc
Power consumption	70 W	130 W
Capacitor	NA	NA
Max. number of operations/day	30	30
Control electronics	Integrated with LCD display	Integrated with LCD display
Operating temperature	-20°C to +60°C	-20°C to +60°C
Protection factor	IP 44	IP 44
RTS remote control frequency	433.42 Mhz	868-870 Mhz
Number of remote controls that can be memorized	36	36

Packs

Elixo 500 3S motor + 2 Keygo	Keygo io	Backup battery	Amber light Master Pro 24 V antenna io	Photocells Master Pro Bitech
	Ref. 1841134	Ref. 9001001	Ref. 9016924	Ref. 1841155

Comfort pack RTS

	•	• 2x	•	•	•
--	---	------	---	---	---